

# openWRT (Wireless) Repeater

## /etc/config/network

```
config 'switch' 'eth0'
    option 'enable' '1'
config 'switch_vlan' 'eth0_0'
    option 'device' 'eth0'
    option 'vlan' '0'
    option 'ports' '0 1 2 3 5'
config 'switch_vlan' 'eth0_1'
    option 'device' 'eth0'
    option 'vlan' '1'
    option 'ports' '4 5'
config 'interface' 'loopback'
    option 'ifname' 'lo'
    option 'proto' 'static'
    option 'ipaddr' '127.0.0.1'
    option 'netmask' '255.0.0.0'
config 'interface' 'lan'
    option 'type' 'bridge'
    option 'ifname' 'eth0.0'
    option 'proto' 'static'
    option 'netmask' '255.255.255.0'
    option 'ipaddr' '192.168.0.1'
config 'interface' 'wan'
    option 'ifname' 'eth0.1'
    option 'proto' 'dhcp'
config 'interface' 'wwan'
    option 'proto' 'dhcp'
```

## /etc/config/wireless

```
config 'wifi-device' 'wl0'
    option 'type' 'broadcom'
    option 'txpower' '18'
    option 'hwmode' '11bg'
    option 'channel' '11'
config 'wifi-iface'
    option 'ssid' 'f00b4r'
    option 'device' 'wl0'
    option 'mode' 'sta'
    option 'network' 'wwan'
    option 'key' '(4xx3ss-2-the-d0me)'
    option 'encryption' 'psk2+tkip+ccmp'
config 'wifi-iface'
    option 'device' 'wl0'
    option 'mode' 'ap'
```

```
option 'encryption' 'none'
option 'ssid' 'OpenWrt-Repeater'
option 'network' 'lan'
```

## /etc/config/dhcp

```
cconfig dnsmasq
    option domainneeded      1
    option boguspriv         1
    option filterwin2k        0 # enable for dial on demand
    option localise_queries  1
    option rebind_protection 1 # disable if upstream must serve RFC1918
addresses
    option rebind_localhost  1 # enable for RBL checking and similar
services
    #list rebind_domain example.lan # whitelist RFC1918 responses for
domains
    option local    '/lan/'
    option domain   'lan'
    option expandhosts 1
    option nonegcache 0
    option authoritative 1
    option readethers 1
    option leasefile   '/tmp/dhcp.leases'
    option resolvfile  '/tmp/resolv.conf.auto'
    #list server       '/mycompany.local/1.2.3.4'
    #option nonwildcard 1
    #list interface     'br-lan'
    #list notinterface  'lo'
    #list bogusnxdomain '64.94.110.11'
config dhcp lan
    option interface    lan
    option start        100
    option limit        150
    option leasetime    12h
config dhcp wan
    option interface    wan
    option ignore       1
```

## /etc/config/firewall

</code>

config 'defaults'

```
option 'syn_flood' '1'
option 'input' 'ACCEPT'
option 'output' 'ACCEPT'
option 'forward' 'REJECT'
```

```
config 'zone'
```

```
    option 'name' 'lan'  
    option 'network' 'lan'  
    option 'input' 'ACCEPT'  
    option 'output' 'ACCEPT'  
    option 'forward' 'REJECT'
```

```
config 'zone'
```

```
    option 'name' 'wan'  
    option 'input' 'REJECT'  
    option 'output' 'ACCEPT'  
    option 'forward' 'REJECT'  
    option 'masq' '1'  
    option 'mtu_fix' '1'  
    option 'network' 'wan wwan'
```

```
config 'forwarding'
```

```
    option 'src' 'lan'  
    option 'dest' 'wan'
```

```
config 'rule'
```

```
    option 'name' 'Allow-DHCP-Renew'  
    option 'src' 'wan'  
    option 'proto' 'udp'  
    option 'dest_port' '68'  
    option 'target' 'ACCEPT'  
    option 'family' 'ipv4'
```

```
config 'rule'
```

```
    option 'name' 'Allow-Ping'  
    option 'src' 'wan'  
    option 'proto' 'icmp'  
    option 'icmp_type' 'echo-request'  
    option 'family' 'ipv4'  
    option 'target' 'ACCEPT'
```

```
config 'rule'
```

```
    option 'name' 'Allow-DHCPv6'  
    option 'src' 'wan'  
    option 'proto' 'udp'  
    option 'src_ip' 'fe80::/10'  
    option 'src_port' '547'  
    option 'dest_ip' 'fe80::/10'  
    option 'dest_port' '546'
```

```
option 'family' 'ipv6'
option 'target' 'ACCEPT'
```

config 'rule'

```
option 'name' 'Allow-ICMPv6-Input'
option 'src' 'wan'
option 'proto' 'icmp'
list 'icmp_type' 'echo-request'
list 'icmp_type' 'destination-unreachable'
list 'icmp_type' 'packet-too-big'
list 'icmp_type' 'time-exceeded'
list 'icmp_type' 'bad-header'
list 'icmp_type' 'unknown-header-type'
list 'icmp_type' 'router-solicitation'
list 'icmp_type' 'neighbour-solicitation'
option 'limit' '1000/sec'
option 'family' 'ipv6'
option 'target' 'ACCEPT'
```

config 'rule'

```
option 'name' 'Allow-ICMPv6-Forward'
option 'src' 'wan'
option 'dest' '*'
option 'proto' 'icmp'
list 'icmp_type' 'echo-request'
list 'icmp_type' 'destination-unreachable'
list 'icmp_type' 'packet-too-big'
list 'icmp_type' 'time-exceeded'
list 'icmp_type' 'bad-header'
list 'icmp_type' 'unknown-header-type'
option 'limit' '1000/sec'
option 'family' 'ipv6'
option 'target' 'ACCEPT'
```

config 'include'

```
option 'path' '/etc/firewall.user'
```

</code>

## Troubleshooting

1. What if openWRT constantly disconnects from the host access point?

This might be related to the fact, that your access points uses the same ESSID on the 2.4GHz as 5GHz channel. The fix is either to disable one of them on your host AP, reconnect 'til it works or check for

another openWRT version for your device.

It might also be that the openWRT wireless host is not on the same channel as the host AP.

1. The 'Associated Stations' shows a '?' below the IP Address field of an entry.

Looks like a bug in the openWRT GUI. Ignore it and verify it via ssh on the access point.

From:  
<https://wiki.c3l.lu/> - Chaos Computer Club Lëtzebuerg



Permanent link:  
<https://wiki.c3l.lu/doku.php?id=projects:howtos:openwrt-repeater&rev=1436402216>

Last update: **2015/07/15 21:54**